



ARBO Engineering Inc.
3 Whitehorse Road Unit 5
Toronto ON M3J 3G8
Canada

Tel (416) 636-7057
Fax (416)-630-9135
www.arbo-feeders.com

WHAT'S NEW AT ARBO?

NEW VIBRATORY DRIVE



AF-30 WP



An extension of ARBO's standard vibratory drives AF14 and AF15 as a result of ARBO's foray in the food industry, the body of this new drive is made entirely of stainless steel, assembled with high precision components for the most demanding application.

The new single cable construction replaces the previous dual cable, enabling a better cable gland seal.

ARBO - *Your difficult material specialist*



ARBO Engineering Inc.
3 Whitehorse Road Unit 5
Toronto ON M3J 3G8
Canada

Tel (416) 636-7057
Fax (416)-630-9135
www.arbo-feeders.com

WHAT'S NEW AT ARBO?

Technical Data:

Total Unit Weight:	17 kg (without counter weights)
Total Unit Weight:	30 kg (with counter weights)
Saddle Weight:	2 kg
Springs:	Fiberglass re-enforced epoxy
Air Gap:	One 2.8 mm, and two 3.5 mm electromagnet: 2.8 mm Tachometer: 4 mm
Protection:	Nema 4X
Working Voltage:	110 VAC or 220 VAC
Power Rating:	
Ambient Temperature:	max. 60°C (140°F) Note: Units for higher temperature are available on special order
Tray Weight:	in normal position maximum 15 kg in inverted position maximum 20 kg
Typical achievable feed rates with a 305 mm wide tray:	infinitely variable between 5 to 5,000 kg/hr For standard palletized material 0.5 kg/dm ³
Turndown Ratio:	1000:1!
To be used with Controller Type:	Vibratory SCR SE-WLS110-2.1/0.5 Vibratory SCR SE-WLS220-2.1/0.5

